


FAX • PRINTER • COPIER • SCANNER • PC FAX













Powerful and Affordable

- Fast Up to 20ppm
- Crisp, Laser Printing
- 250-Sheet Letter or Legal Paper Capacity
- Wide Compatibility Windows® and Mac®



Locoth At your side. Of Colong At your side.

MFC-7220 / MFC-7225N





Key Features at a Glance

MFC-7220

- Up to 20ppm print speed
- Up to 1200 x 600 print resolution
- 16MB (up to 500 pages*) fax memory
- Up to 20-sheet auto document feeder
- 250-sheet paper tray capacity adjustable for letter and legal paper
- 14.4K bps fax
- Mac® and Windows® compatible
- Full-Speed USB 2.0 and Parallel interfaces



MFC-7225N

Includes all of the features of the MFC-7220 plus...

- Built-in internal network board (Ethernet) interface
- Faster fax modem speed (33.6K bps)
- Greater memory capacity
- Greater ADF capacity (Up to 30 sheets)
- PCL6 and BR-S3 (PostScript® Level 3®) emulations





Technical Specification

	energy Parties Technical Specifications								
	ENERGY STAR	MFC-7220	MFC-7225N						
Fax	Modem Speed/Best Transmit Speed*	14.4K bps / 6 sec.	33.6K bps / 2 sec.						
	Color or B&W Faxing	B&W	B&W						
	Auto Document Feed Capacity	20 Pages	30 Pages						
	Paper Capacity	250 Sheets	250 Sheets						
	Paper Size(s)	Letter, Legal, A4, B5, A5, B6, A6, EXE	Letter, Legal, A4, B5, A5, B6, A6, EXE						
	Standard Memory Capacity (Max. Pgs.)*	16MB (500)	32MB (600)						
	Broadcasting (# of Locations)	Yes (up to 260)	Yes (up to 260)						
	Quick Scan (Seconds/Page)*	Yes (3.5 sec.)	Yes (3.5 sec.)						
	Remote Retrieval	Yes	Yes						
	Fax Forwarding/Paging	Yes / Yes	Yes / Yes						
	Dual Access	Yes	Yes						
	One Touch/Speed Dial Locations	10/200	10/200						
	Fax Compatibility	ITU-T G3	ITU-T Super G3						
	Coding Method(s)	MH/MR/MMR	MH/MR/MMR/JBIG						
Print	Printing Method	Laser	Laser						
	Print Speed (Max. ppm)	20ppm	20ppm						
	Print Resolution (Max. dpi)	Up to 1200 x 600	HQ1200 (Up to 2400 x 600)						
	Parallel & Full Speed USB 2.0 Interfaces▼	Yes	Yes						
	Ethernet Interface	Optional† (External)	Standard (Internal)						
	Wireless 802.11b/g Interface	Optional [†] (External)	Optional† (External)						
	Windows® Compatibility	98/98SE, Me, NT® 4.0, 2000, XP	98/98SE, Me, NT® 4.0, 2000, XP						
	Emulation(s)	GDI	PCL6, BR-S3 (Postscript®3 Emulation)						
	Mac® Compatibility	OS 9.1-9.2 [‡] , OS X 10.2.4	OS 9.1-9.2 [‡] , OS X 10.2.4						
		or greater [‡]	or greater [‡]						
Сору	Copy Speed (Max. cpm)	20cpm	20cpm						
	Copy Resolution (Max. dpi)	600 dpi Class	600 dpi Class						
	Sorting Function	Yes	Yes						
	Reduction/Enlargement	50% – 200% in 1% increments	50% – 200% in 1% increments						
Scan	B/W Scanning	Yes	Yes						
	Optical Resolution (Max. dpi)	200 x 400	200 x 400						
	Interpolated Resolution (Max. dpi)	1200 x 1200‡	1200 x 1200 [‡]						
	Driver Provided	TWAIN, WIA (Windows® XP)	TWAIN, WIA (Windows® XP)						
	Document Viewer & OCR Software	PaperPort® OmniPage® for Windows®,	PaperPort® OmniPage® for Windows®,						
		Presto!®PageManager® with OCR for Mac®	Presto!®PageManager® with OCR for Mac®						
Other	PC Fax Software	Yes	Yes						
	LAN Option(s) [†]	NC2100p - 10/100 BaseT External	NC2200w - External wireless print/scan						
		network print server	server (802.11b)						
		NC2200w - External wireless print/scan							
		server (802.11b)							
	Consumable Type† (Max. Yield)	TN350 (approx. 2,500 pgs.▲)●	TN350 (approx. 2,500 pgs.♣)•						
		DR350 (approx. 12,000 pgs*)	DR350 (approx. 12,000 pgs*)						
	Unit Dimensions (W" x D" x H")	14.7 x 14.7 x 10.3	14.7 x 14.7 x 10.3						
	Carton Dimensions (W" x D" x H")	17.8 x 19.4 x 16.9	17.8 x 19.4 x 16.9						
	Unit/Carton Weight (lb.)	16.3/23.8	16.3/23.8						

Minimum System Requirements and Supported PC Software Functions										
Computer Platform & Operating System Version		Supported PC Software Functions	PC Interface	Processor Minimum Speed	Minimum RAM	Recommended RAM	Available Hard Dlsk Space			
							For Drivers	For Applications		
Vindows® Operating System¹	98, 98SE	Printing, PC Fax³, Scanning⁴	USB, Parallel, Ethernet	Pentium II or equivalent	32 MB	64 MB	- 90 MB	130 MB		
	Me		USB, Parallel, Ethernet							
	NT® Workstation 4.0		Parallel, Ethernet		64 MB	128 MB				
	2000 Professional		USB, Parallel, Ethernet							
	ХР		USB, Parallel, Ethernet		128 MB	256 MB	150 MB	220 MB		
Mac [®] Operating Systems	OS 9.1 – 9.2	Printing, PC Fax send, Scanning ²	USB Ethernet	All base mo minimum req		64 MB	80 MB	200 MB		
	OS X 10.2.4 or greater	Printing, PC Fax send,	USB		128 MB	160 MB				

"Ethernet only applies to MFC-7820N.
"Microsoft" Internet Explorer 5 or greater.
"Dedicated "Scan" key functions only in Mac OS" X 10.2.4 or greater.
"PC Fax send only for network users.
"Network Scanning not supported in Windows NT" Workstation 4.0.

For the latest drivers, access the **Brother Solutions Center at** http://solutions.brother.com

UPC Code

Optional Supplies and Accessories[†]

0 12502 61328 2

TN350: Standard Toner Cartridge (approx. 2,500 page yield*)
Replacement Drum Unit
(approx. 12,000 page yield*)
10/100 BaseT External Network Print Server DB350: NC2100p: External Wireless Print/Scan Server (802.11b)

- Based on Brother No.1 Chart with MMR (MFC-7220) or JBIG (MFC-7225N) coding at standard resolution in ECM. Requires additional purchase. Cables not included.

0 12502 61327 5

- oprox. vield based on 5% page coverage. Imes with Starter Toner Cartridge (approx. 1,500 page yield @5% page verage). e minimum system requirement about 1500 page yield @5% page
- See minimum system requirement chart for details May vary by usage type.

For more information please visit our Web site at www.brother.com

