


intelliFAX[®]-3800

LASER PLAIN PAPER FAX,
PHONE & COPIER

FEATURING

- Up to 10 ppm Laser Engine for Printing of Copies and Faxes
- 33.6K bps High Speed Fax Modem
- 8MB, Dual Access Memory
- 30 Page Automatic Document Feeder
- 200 Sheet Paper Cassette



At your side.[™]


brother[®]

intelliFAX[®]-3800

LASER PLAIN PAPER FAX, PHONE & COPIER


Featuring...

- Up to 10 ppm Laser Engine for Printing of Copies and Faxes
- 33.6K bps High Speed Fax Modem
- 8MB, Dual Access Memory with 7-Day Back-up
- 30-Page Automatic Document Feeder
- 200 Sheet Paper Cassette Capacity
- Stores up to 600 Pages* for Out-Of-Paper Reception and Quick Scan
- 128 Station Auto Dialing
- Broadcasting to up to 178 Locations
- Parallel & USB Interfaces for Future Printing Needs**
- 10 cpm Multi-copying (up to 99)
- Copy reduction and enlargement (50% – 200%)
- Caller ID and Distinctive Ring Detection ready▼
- Economical replacement toner cartridges deliver low cost per page



Other Standard Features

- Fax Forwarding, Paging and Remote Retrieval
- Navigation keys for menus, options and index dialing
- Electronic Cover Page
- Multiple Resolution Transmission
- Enhanced Remote Activation
- "Smoothing" Enhanced Image Resolution
- Answering Machine Interface
- Built-in Telephone Handset
- Polling and Delayed Transmission
- Error Correction Mode (ECM)
- Auto reduction of incoming faxes
- Special offer included from CallManage[™] for "One-Touch" Internet Calling and Faxing†



* Using Brother #1 chart with MMR coding and standard resolution.

** Printer Driver available on Brother web site.

▼ Contact local phone company for availability of these services.

† Requires change of carrier to CallManage, Inc. This feature may not be available in some parts of the USA and is not available in Canada. Brother International Corp. is not responsible for long distance services or customer billing. See complete terms and conditions inside Owner's Manual.



PRODUCT SPECIFICATIONS

Approved:	UL and FCC
Unit Dimensions:	15.6" x 14.1" x 9.6"
Unit Weight:	16.5 lbs.
Carton Dimensions:	17.9" x 20.4" x 14.8"
Carton Weight:	24.2 lbs.
UPC Code:	0 12502 60060 2
Compatibility:	Group 3 ITU-TS
Coding Method:	MH/MR/MMR/JBIG
Modulation:	33600, 31200, 28800, 26400, 24000, 21600, 19200, 16800, 14400, 12000, 9600, 7200, 4800, 2400 bps
Transmission Time:	2 seconds (8.5" x 11")*
Document Input Size:	5.8" to 8.5"
Recording Paper Size:	8.5" x 11"/8.5" x 14"
Effective scanning/Printing Width:	8.2"
Resolution: Standard:	203 x 98 lines/inch
Fine Mode:	203 x 196 lines/inch
Super Fine:	203 x 392 lines/inch
Display:	16 character backlit LCD
Dialing System:	Selectable Pulse/Tone
Speaker Type:	Monitor
Communication Source:	Public Switched Telephone Network
Communication Requirements:	USOC RJ11C Modular Jack (or equivalent)
Power Supply:	120V, 50/60Hz
Power Consumption:	Sleep Mode: 10W or less Standby: 70W or less Avg. Operating: 260W or less
Noise Level:	Operating: 50 dbA or less Standby: 39 dbA or less
Operating Environment:	50° to 90.5° (F)

OPTIONAL ACCESSORIES†

TN250:	Replacement Toner Cartridge (2,200 pages per cartridge*)
DR250:	Replacement Drum Unit

† Requires additional purchase

▲ Based on 5% page coverage

use only
GENUINE
brother
supplies

At your side.[™]
brother[®]

www.brother.com

© 2001 BROTHER INTERNATIONAL CORPORATION, 100 Somerset Corporate Blvd., Bridgewater, NJ 08807-0911

For more information please call the Brother Fax-Back System at 1-800-521-2846 (USA),

1-800-681-9838 (CANADA) or visit our web site at www.brother.com.

All specifications are subject to change without notice. Printed in USA. CATFX3800