HL-3045cN Digital Color Printer







HL-3045cN Digital Color Printer with Networking

The HL-3045cN is ideal for home offices or small offices. It produces brilliant, high-quality output at a fast print speed of up to 19ppm in color or black. This compact printer offers versatile paper handling with a 250-sheet capacity paper tray for letter or legal and a single-sheet manual feed slot for envelopes or thicker media. It has a built-in Ethernet network interface for sharing with others on your network and also a top-loading design to easily replace and install toner cartridges.

Technical Specifications		
		HL-3045см
General	Print Technology	Digital Color LED
	Print Speed (max.)	19ppm in color or black
	Time to First Page≻	< 15 seconds in monochrome, < 16 seconds in color
	Print Resolution (max.)	600 x 2400 dpi
	Memory (std. / max.*)	32MB / 544MB
	Processor	NEC VR5500 300MHz
	Printer Emulations	GDI
	Standard Interfaces	Ethernet, USB
Paper Handling [‡]	Standard Input Capacity	250-sheet capacity paper tray, single-sheet by-pass slot
	Output Capacity	100 sheets (face down), 1 sheet (face up)
	Paper Sizes	Letter, legal, executive, A4, and envelopes Custom sizes via manual feed slot: 3.0" to 8.5" (w), 4.57" to 14" (l)
	Media Types	Plain paper, recycled paper, bond, envelopes, labels
	Media Weights	Standard paper tray: 16 to 28 lbs. (bond) Manual feed slot: 16 to 43 lbs. (bond)
Software*	Defeator Defeator	Windows® 7 / Windows Vista®/ XP/ XP Professional x64 Server 2003, Server 2008 / 2008 R2
	Printer Drivers	Mac OS® X 10.4.11 or 10.7.x Linux: Red Hat, Mandrake, SuSE, Debian
	Print Settings	Toner Save, Power Save, N-Up, Watermark, Poster, Job Cancel, Reprint
	Security Functions	Secure Print
	Other Software	Interactive Help, Driver Deployment Wizard
Networking	Network Compatibility	TCP/IP (IPv4/IPv6), Apple® Simple Network Configuration
	Network Management Tools	BRAdmin Light, Web-based Management, BRAdmin Professional [†] , Web-BRAdmin [†] ◆
Electrical	Power Requirements	120 VAC +/- 10% 50/60 Hz
	Power Consumption (Avg.)	Printing: 480W / Ready: 70W / Sleep: 8W
	ENERGY STAR® Qualified	Yes
Environ.	Temperature	50°F to 90.5°F (10°C to 32.5°C)
	Humidity	20% - 80% (without condensation)
	Noise Level	Sound Pressure: Printing: LpAm= 53 dB; Ready: LpAm= 30 dB Sound Power: Printing: LWAd= 6.3B; Ready: LWAd= 3.6B
Other	LCD Display	Yes (1 line, 16 characters)
	Unit Dimensions (W" x D" x H")	16.1" x 18.3" x 9.8"
	Carton Dimensions (W" x D" x H")	24.7" x 21.9" x 18.1"
	Unit Weight / Carton Weight	41.9 lbs. / 48.5 lbs.
	UPC Codes	0 12502 63092 0
	Warranty / Service	One-year express exchange limited / parts and labor

Key Features at a Glance:

- · Prints up to 19ppm in color and black
- Up to 600 x 2400 dpi resolution
- · Built-in Ethernet and Hi-Speed USB 2.0 interfaces
- Adjustable 250-sheet capacity paper tray
- 32MB memory standard, expandable*
- Top-loading design for quick and easy toner replacement
- · Toner-Save mode









brothe

Supplies and Accessories*

TN-210BK: Black Toner Cartridge (2,200 pages)*
TN-210C: Cyan Toner Cartridge (1,400 pages)*
TN-210Y: Yellow Toner Cartridge (1,400 pages)*
TN-210M: Magenta Toner Cartridge (1,400 pages)*
DR-210CL: Belt Unit (50,000 pages)^
BH-200CL: Belt Unit (50,000 pages A4/Letter)
WT-200CL: Waste Toner Box (50,000 pages)^
BP60MPLTR: Multi-Purpose Paper (500 sheets, letter)

For full technical specifications and more information, please visit www.brother.com.

- Additional purchase required
- From ready mode and standard tray
- * All references to sheets of paper refer to 20 lb (bond) paper.
- Some advanced features are not supported under all operating systems or drivers. See User's Guide on-line for details
 Download at http://solutions.brother.com
- Requires IIS Server
- Approx. yield in accordance with ISO/IEC 19798 (Letter/A4). Printer ships with a starter cartridge (approx. 1,000 pages)
- Drum yield is approx. and may vary by type of use
- Approximate yield based on A4 or Letter size single-sided pages

© 2011 Brother International Corporation, 100 Somerset Corporate Blvd., Bridgewater, NJ 08807-0911. PostScript is a trademark of Adobe Systems, Inc. Mac and the Mac logo are trademarks of Apple Inc., registered in the U.S. and other countries. Microsoft, Windows, and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries. Windows Vista® is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. All brand and product names are trademarks or registered trademarks of their respective companies. Images are for illustrative purposes only. All specifications subject to change without notice. CATHI 3045CN 12/11

