

PRINTER • FAX • COPIER • SCANNER • PC FAX





## MFC-3100c

- Black and White or Color Faxing (using ITU-T30E standard)
- 20 Page Auto Document Feeder
- 14.4K bps high-speed fax modem
- Broadcasting (up to 90 locations)
- 40 station auto dialing
- 2MB Total Memory (up to 100 pages\*)
- Dual Access lets you scan a fax into memory while another is being received
- Simultaneous Operations let you perform two functions at once

# COLOR PRINTER

- Up to 10 pages per minute black or 8 pages per minute color printing
- Up to 2400 x 1200 dpi resolution
- Parallel and USB interfaces standard (cables not included)
- 100 Sheet Paper Cassette
- Works with Windows® and iMac™/iBook™/G3/G4 (see minimum system requirements below)







## COLOR COPIER

- Convenient black and white or full color copies
- Up to 1200 x 1200 dpi resolution
- Multi-copying, up to 99
- Reduce or enlarge from 25% to 400% in one percent increments

## COLOR SCANNER FEATURES

- Includes award-winning ScanSoft™ PaperPort® and TextBridge® OCR software
- Up to 2400 dpi (Interpolated) resolution
- Up to 300 x 600 dpi (Optical) resolution
- Easy to use desktop interface with "drag and drop" filing and linking
- Works with Windows® and iMac™/iBook™/G3/G4

(see minimum system requirements below)

# **EATURES**

- Includes Brother PC Fax Driver for sending faxes from your PC
- Broadcast faxes from your PC
- Works with Windows® and iMac™/iBook™/G3/G4

## MFC-3100c Optional Supplies & Accessories

LC21BK	Black Ink Cartridge	use only
LC21Y	Yellow Ink Cartridge	GENUINE
LC21C	Cyan Ink Cartridge	brother supplies
LC21M	Magenta Ink Cartridge	20bbne2
BP72CL	720 dpi Ink Jet Paper (200 sheets)	
BPGLL	High Quality Glossy Paper (20 sheets)	
BPTRL	Transparency Sheets (50 sheets)	

<sup>\*</sup> Based on Brother #1 Chart with MMR coding and standard resolution.

### Minimum System Requirements Computer Platform & Operating System Version Available Hard Disk Space linimun RAM 95, 98, 98SE Pentium 75MHz 24MB 32MB 50MB 2X Windows® □ Me 64MB Pentium 150MHz 32MB 50MB 2X **Operating** NT® Workstation 4.0 Pentium 75MHz 32MB 64MB 50MB 2X **Systems** 2000 Professional Pentium 133MHz 64MB 128MB 50MB 2X Pentium 233MHz 64MB 128MB 50MB 2X Apple 50MB 2X OS 8.5, 8.5.1 (Printer Only) iMac™/iBook™/ 50MB 2X All base models meet minimum requirements G3/G4 Operating OS 8.6 - 9.1 (Printer & Scanner) Systems 2X

NOTE: USB is not supported under Windows® 95 or Windows NT® 4.0

All registered trademarks referenced herein are the property of their respective companies.

## © 2001 BROTHER INTERNATIONAL CORPORATION

100 Somerset Corporate Blvd., Bridgewater, NJ 08807-0911

For more information please call the Brother Fax-Back System at 1-800-521-2846 (USA), 1-800-681-9838 (Canada), or visit our web site at www.brother.com All specifications are subject to change without notice. Printed in USA. CATMFC3100C



### PRODUCT SPECIFICATIONS

Approved: FCC & UL

Unit Dimensions: 16.8" x 13.5" x 8.5" Carton Dimensions: 20.4" x 18.0" x 14.8" Unit/Carton Weight: 14.3 lbs/23.1 lbs

UPC Code: 0 12502 56581 9

Printing Method/Speed: Color Ink Jet/Up to 10 ppm (B&W)

Compatibility: ITU Group 3 Coding Method: MH/MR/MMR/JPEG Modulation: 14400/12000/9600/ 7200/4800/2400 bps

Transmission Time: 6 seconds (ITU #1 chart) MMR

Total Machine Memory: 2MB Document Input Width: 5.8" to 8.5"

Recording Paper Size: 8.5" x 11"/8.5" x 14"

Paper Type for Manual Pass: Letter, Legal, A4, B5, Executive,

Envelopes, Transparencies, Custom Size 3.5" x 5" to 8.5" x 14"

Scanning & Recording Width: 8.2"

Printer Resolution (max.): True 2400 x 1200 dpi Fax Resolution: Standard: 203 x 98 lines/inch Fine: 203 x 196 lines/inch

Superfine: 203 x 392 lines/inch

Gray Scale/Color Depth: 256 shades/30 bit

Speaker Type: Monitor

Interfaces (standard): High-Speed Bi-Directional

Centronics Parallel & USB interfaces (cables not included)

**Emulations: None** 

Utility Software: Windows® 95/98/98SE, Me,

NT® Workstation 4.0, 2000 Professional, XP, or iMac™/iBook™/G3/G4, OS 8.5-9/1▼

Power Supply: 120V, 50/60Hz

Power Consumption: Operating (Peak): 35W or less

Standby: 7W or less

Noise Level: 48dbA (printing)

Operating Environment: 50° to 95° (F)

OS 8.5, 8.5.1 support printing only.

