

FAX • LASER PRINTER • DIGITAL COPIER • COLOR SCANNER • PC FAX



At your side.

At your side.

R

# 

### MFC-6800

# **FEATURES**

- 30 Page Auto Document Feeder
- Super Quick Scan up to 3 seconds per page\*
- 14.4K bps High-Speed Fax Modem
- 100 Station Auto Dialing
- 8MB Total Memory (up to 500 pages\*)
- Broadcasting (up to 150 locations)
- Dual Access lets you scan a fax into memory while another is being received
- Simultaneous Operations let you perform two functions at once

#### LASER PRINTER **FEATURES**

- Up to 10 pages per minute Printing
- True 600 x 600 dpi Laser Output
- Parallel and USB Interfaces Standard (cables not included)
- 200 Sheet Paper Cassette Capacity
- Works with Windows® and iMac™/ iBook™/G3/G4 applications (see minimum system requirements below)





#### DIGITAL COPIER **FEATURES**

- Versatile Flatbed Design for copying from bound documents
- Up to 10 cpm Copy Speed
- 600 dpi Copy Output
- No PC required
- Multi-Copying, up to 99, with Sorting
- Reduce or enlarge from 25% to 400% in one percent increments

# LOR SCANNER

- Flatbed Design for scanning from bound documents
- Color or Black & White Scanning
- Up to 9600 x 9600 dpi (Interpolated) Resolution and up to 600 x 2400 dpi (Optical) Resolution
- Easy to use Desktop interface with "Drag and Drop" Filing and Linking
- Includes award-winning ScanSoft™ PaperPort® and TextBridge® OCR software

# **FEATURES**

- Includes Brother PC Fax Software for sending faxes from your PC
- Broadcast faxes from your PC
- Works with Windows® and iMac™/iBook™/G3/G4

## MFC-6800 Optional Supplies & Accessories<sup>†</sup> brother

TN-250 Standard Toner Cartridge 2,200 pages per cartridge

Drum Unit

\*Based on Brother #1 Chart with MMR coding and standard resolution <sup>†</sup>Requires additional purchas

▼Based on 5% page coverage

#### **Minimum System Requirements** Computer Platform & Operating System Version Minimui RAM Disk Sna 95, 98, 98SE Pentium 75MHz 24MB 32MB 50MB 2X Windows® Me 32MB Pentium 150MHz 64MB 50MB 2X Operating NT® Workstation 4.0 Pentium 75MHz 32MB 64MB 50MB 2X **Systems** 2000 Professional Pentium 133MHz 64MB 128MB 50MB 2X Pentium 233MHz ΧP 64MB 128MB 50MB 2X Apple 2X OS 8.5, 8.5.1 (Printer Only) iMac™/iBook™/ 50MB 2X All base models meet minimum requirements G3/G4 Operating OS 8.6 - 9.1 (Printer & Scanner) **Systems** 2X

NOTE: USB is not supported under Windows® 95 or Windows NT® 4.0 All registered trademarks referenced herein are the property of their respective companies

#### © 2001 BROTHER INTERNATIONAL CORPORATION

100 Somerset Corporate Blvd., Bridgewater, NJ 08807-0911

For more information please call the Brother Fax-Back System at 1-800-521-2846 (USA), 1-800-681-9838 (Canada), or visit our web site at www.brother.com All specifications are subject to change without notice. Printed in USA. CATMFC6800



Approved: FCC & UL Unit Dimensions: 18.1" x 18.0" x 12.5" Carton Dimensions: 22.3" x 23.5" x 17.8" Unit/Carton Weight: 24.2 lbs/35.2 lbs

UPC Code: 0 12502 56580 2

Printing Method/Speed: Electrophotography/10PPM

Compatibility: ITU Group 3 Coding Method: MH/MR/MMR Modulation: 14400/12000/9600/ 7200/4800/2400 bps

Transmission Time: 6 seconds (ITU #1 chart) MMR

Total Machine Memory: 8MB Document Input Width: 5.8" to 8.5"

Recording Paper Size: 8.5" x 11"/8.5" x 14"

Paper Type for Manual Pass: Letter, Legal, A4, B5, Executive,

Envelopes, Transparencies, Laser label sheets, Custom Size 2.75" x 5" to 8.5" x 14"

Scanning & Recording Width: 8.2"

Printer Resolution: True 600 x 600 dni Fax Resolution: Standard: 203 x 98 lines/inch Fine: 203 x 196 lines/inch

Superfine: 203 x 392 lines/inch

Gray Scale: 64 shades Speaker Type: Monitor

Interfaces (standard): High-Speed Bi-Directional

Centronics Parallel & USB interfaces (cables not included)

**Emulations: Brother Printing Solution for** Windows® or iMac™/iBook™/G3/G4

Utility Software: Windows® 95/98/98SE, Me, NT® Workstation 4.0,

2000 Professional, XP, or

iMac™/iBook™/G3/G4, OS 8.5-9/14 Power Supply: 120V, 50/60Hz

Power Consumption: Operating (Copying): 260W or less Standby: 75W or less

Sleep Mode: 15W or less

Noise Level: 50 dbA (printing) 39 dbA (standby)

Operating Environment: 50° to 90.5° (F)

◆OS 8.5. 8.5.1 support printing only.

