

At your side. Colonial At your side. Reserved to the second sec

intellifAX-29

PLAIN PAPER FAX,
PHONE & COPIER

Featuring...

- Up to 10 ppm Laser Engine for Printing of Copies and Faxes
- 14.4K bps Fax Modem
- 4MB, Dual Access Memory with 7-Day Back-up
- 30 Page Automatic Document Feeder
- 200 Sheet Paper Cassette Capacity
- Stores up to 300 Pages* for Out-Of-Paper Reception and Quick Scan
- 128 Station Auto Dialing
- Fax Broadcasting to up to 178 Locations
- Parallel and USB Interfaces for Future Printing Needs**
- Fax Forwarding, Paging and Remote Retrieval
- Multi-copying (up to 99 copies)
- Copy Enlargement to 200%, Reduction to 50% (in 1% increments)
- Economical replacement toner cartridges deliver low cost per page
- Navigation keys for menus, options and index dialing





Other Standard Features



- Call Waiting/Caller ID and Distinctive Ring Detection ready[▼]
- Automatically receives fax and voice calls on the same phone line
- Built-in Telephone Handset
- Electronic Cover Page
- Multiple Resolution Transmission
- Enhanced Remote Activation
- "Smoothing" Enhanced Image Resolution
- Answering Machine Interface
- Polling and Delayed Transmission
- Error Correction Mode (ECM)
- Special offer included from CallManage™ for "One-Touch" Internet Calling and Faxing[†]



- ** Printer Driver available on Brother web site.
- ▼ Contact local phone company for availability of these services.

* Using Brother #1 chart with MMR coding and standard resolution.

Requires change of carrier to CallManage, Inc. This feature may not be available in some parts of the USA and is not available in Canada. Brother International Corp. is not responsible for long distance service or customer billing. See complete terms and conditions inside Owner's Manual.



Approved: UL and FCC Unit Dimensions: 15.6" x 14.1" x 9.6" Unit Weight: 16.5 lbs.

Carton Dimensions: 17.9" x 20.4" x 14.8"

Carton Weight: 24.2 lbs. UPC Code: 0 12502 60074 9 Compatibility: Group 3 ITU-TS Coding Method: MH/MR/MMR

Modulation: 14400/12000/9600/7200/4800/2400 bps

Transmission Time: 6 seconds per page* Document Input Width: 5.8" to 8.5" Recording Paper Size: 8.5" x 11", 8.5" x 14"

Effective Scanning Width: 8.2"

Fax Resolution: Standard: 203 x 98 lines/inch Fine Mode: 203 x 196 lines/inch Superfine: 203 x 392 lines/inch

> Gray Scale: 64 shades Display: 16 character LCD

Communication Source: Public Switched Telephone Network

Speaker Type: Monitor

Communication Requirements: USOC RJ11C Modular Jack

(or equivalent)

Dialing System: Tone Power Supply: 120V, 50/60Hz

Power Consumption: Sleep Mode: 10W or less Standby: 70W or less

Avg. Operating: 260W or less

Noise Level: Operating: 50 dbA or less

Standby: 39 dbA or less

use only

GENUINE

Operating Environment: 50° to 90.5° (F)

OPTIONAL ACCESSORIES[‡]

TN250: Replacement Toner

Cartridge

(2,200 pages per cartridge-) DR250: Replacement Drum Unit

‡ Requires additional purchase

▲ Based on 5% page coverage





