# **Commercial / Industrial**

# Computer **Label Printer**



Advanced printing features allow you to produce crisp text, bar codes and more, on crack and peel laminated labels - fast.



### Perfect for:

- Asset management
- Property management
  Manufacturing
  Telecom & datacom
  General office





- Includes PT-Editor software with predesigned label templates for easy label creation
- New half-cutter allows easy-to-remove backing
- Professional formatting features
- Print labels from databases
- 16 industry-standard bar codes
- Easy USB or serial connection to your PC or Mac®







At your side. Orot



# **Model PT-9500PC Electronic Labeling System**

### PT-9500PC Specifications

#### **PRINTING FEATURES**

- Crisp, professional-quality 360 dpi printing of text and graphics
- Prints durable laminated labels from 1/4" to 11/2" wide
- Prints Avery® address, return address, and file folder labels\* simply by switching cassettes
- Prints from Microsoft and text-formatted databases (\*.csv, \*.xls, \*.mdb)
- Prints 1 line at 91 point size (1.1") or up to 16 lines

#### **LABEL-DESIGN FEATURES**

- Includes pre-designed telecom/datacom and other industry templates plus hundreds of industrial and business symbols and clip art
- Design and save your own custom templates
- Accepts all TrueType® fonts
- Prints 16 scannable ANSI x3.182 compliant bar code symbologies
- Prints .gif, .jpg, JPEG, TIF/TIFF and other graphic formats
- Import text and graphics from leading office software suites
- Prints serialized alpha/numeric labels

#### **EASE-OF USE FEATURES**

- Built-in automatic cutter (makes easy-peel labels)
- Uses interchangeable TZ and AV tape cassettes
- Includes USB and RS-232C serial interfaces for connection to a computer
- Compatible with Windows 98/Me/2000 Professional/XP and Mac OS 8.6 to 9.x, OS X 10.1 to 10.2.6

#### **CARTON CONTENTS**

- PT-9500PC Label Printer
- AC Adapter
- Serial Interface Cable
- CD (Design Software & Drivers)
- Tape Catch Tray
- USB Cable
- One TZ261 1½" Black on White TZ Laminated Tape

One year limited warranty

Data Matrix

Laser Bar

Code

#### **SPECIFICATIONS**

- Powered by AC Adapter (included)
- Unit Weight: 1.2Kg / 2.64 lbs.
- Unit Dimensions: 4.6"(w) x 5"(h) x 7.5"(d)

### 16 BAR CODES

- CODE39
- 1-2/5(ITF)
- UPC-AUPC-EEAN13
- EAN8CODABAR
- (NW-7)
- CODE128
- CODE12
- EAN128
- POSTNET
- ISBN-2
- ISBN-5
- DDE445
- PDF417
- QRCODE
- PT-9500PC SYSTEM REQUIREMENTS Microsoft® Windows® Macintosh Port Serial port (RS-232C) USB 1.1 port USB 1.1 port Installed with Microsoft® Pre-installed with Installed with Mac Windows® 95†, NT 4.0†, 98, 98SE, Me, 2000 Pro Microsoft® Windows® OS 8.6 to 9.x or Mac OS X 10.1 to 10.2.6, Operating 98, 98SE, Me, 2000 Pro **System** or XP or XP and equipped with a USB port as standard equipment Minimum of 24 MB Minimum 64 MB Memory of available memory Minimum of 100 MB Hard-Disk Minimum of 70 MB of available hard-disk space<sup>††</sup> of available hard-disk Free Space Others CD-ROM drive (required to install the software)

### Uses interchangeable TZ tape cassettes.\*

# Standard Adhesive Tape – Laminated For Flat, Smooth Surfaces, Indoors and Outdoors

Perfect for labeling:

• File folders and binders • Name badges • Small signage

Our standard adhesive tapes are designed for flat, smooth surfaces, and resist water, grease or grime – the laminated surface wipes clean – and fading and abrasion. They also withstand temperatures from -30 to 100 degrees C and can be used for indoor and outdoor applications.



26.2' long, unless otherwise noted	1/4 "	3/8 "	1/2 "	3/4 "	1"	1 1/2 "
BLACK ON WHITE	<b>4</b>	1	<b>4</b>	1	1	1
BLACK ON CLEAR	1	1	1	<b>4</b>	1	<b>4</b>
BLACK ON CLEAR MATTE				1		
BLACK ON RED		1		1	1	
BLACK ON YELLOW			1	1	1	1
BLACK ON GREEN				<b>V</b>		
BLACK ON BLUE				1		
BLACK ON FL. ORANGE				1	1	
WHITE ON BLACK	1	<b>V</b>	1	<b>V</b>	1	
WHITE ON OLEAR *			1	<b>✓</b>		
WHITE ON BLUE				<b>✓</b>		
RED ON WHITE			1	<b>✓</b>	1	
BLUE ON WHITE				<b>V</b>		
GOLD ON BLACK			1	1	1	

#### Extra Strength Adhesive Tape - Laminated

For Tough Applications – With up to 2x the adhesion strength of our standard laminated labels

### Perfect for labeling:

- · Harsh environments
- A variety of plasticsTextured surfaces
- Painted surfaces

ON CT PLIES PICING	0	1/4" Nut
		14472341434000

26.21 long	1/4 "	3/8 "	1/2 "	3/4 "	1"	1 1/2 '
BLACK ON WHITE	<b>V</b>	<b>V</b>	1	<b>V</b>	1	1
BLACK ON CLEAR	1	1	1	1	1	1
BLACK ON YELLOW	<b>-</b>	1	<b>4</b>	<b>V</b>	1	1
WELTE ON GLEER			1	<b>V</b>	1	
BLACK ON MATTE SILVER				1	1	1

# Flexible ID Tape – Laminated Special Adhesive For Bending, Wrapping & Flagging Perfect for labeling: • Cable & wire • Vials, beakers & test tubes • Electrical fittings and connectors\* • Not suitable as an electrical insulator 26.2\* long 1/4 \*\* 3/8 \*\* 1/2 \*\* 3/4 \*\* 1\*\* 11/2\*

BLACK ON WHITE



For a system with Microsoft® Windows® NT 4.0, 2000 Pro or XP, be sure to install it from an account with administrator privileges.

- With Microsoft<sup>®</sup> Windows<sup>®</sup> 95 and NT 4.0, connection is possible only from a serial port. Internet Explorer 3.02 or later is required for installation. In addition, when using NT 4.0, Service Pack 6 or later must be installed, and Internet Explorer 5.5 is needed for clip art. P-touch Quick Editor and P-touch AV Editor cannot be used with Microsoft<sup>®</sup> Windows<sup>®</sup> 95 and NT 4.0.
- $^{\dagger\dagger}$  The hard-disk free space is required for installing all options. Additional hard-disk space required for HTML manual.
- \* Requires additional purchase

#### For P-touch information, call 1-877-4PTOUCH (1-877-478-6824)

© 2003 Brother International Corporation,100 Somerset Corporate Boulevard, Bridgewater, NJ 08807 All rights reserved. All trademarks and registered trademarks are the property of their respective companies. All specifications subject to change without notice. Printed in U.S.A.

Got questions? Please contact the Product Manager by e-mailing your questions to:

industrial@brother.com



**MODEL PT-9500PC** 



Advanced printing features allow you to produce crisp text, bar codes and more, on crack and peel laminated labels - fast.

ELECTRONIC LABELING SYSTEN



# PT-9500PC Features

# Fast, 360 dpi high-resolution printing

- Prints crisp text and graphics even photos on laminated labels, at up to 20 mm/second
- Prints scannable ANSI x3.182 compliant bar code labels

### New half-cutter — allows easyto-remove backing

- Industrial strength cutter
- Produces easy-peel labels one at a time or in strips



### Professional features

- Easy-to-use industrial, office, telecom/datacom templates
- Auto incrementation feature, for fast serialized labeling

### Print labels from databases

- Accepts \*.mdb, \*.csv, and \*.xls formats

### Easy USB or serial connection to your PC or Mac®

USB cable, serial cable, design software & drivers included

# Includes P-touch® Editor software

Turns your PC or Mac<sup>®</sup> into the ultimate label creation station!

### **Easy-to-Use Label Design Tools**

- Pre-defined telecom/datacom, industrial, and general office templates
- Auto-incrementation for alpha/numeric serialized labels
- · Store commonly and recently used files

## 5C-A12 5C-B24 5C-B24

### **Import Text and Graphics**

- Drag and drop text from other software applications
- Import custom designed .jpg, .jpeg, .bmp, .tiff files

### **Print Bar Codes, Symbols, and Graphics**


- ANSI x3.182 bar codes, 16 standard formats including 2D bar codes
- Industrial symbols and graphics
- Clip art library

# **Import and Print Data from a Database**

• Import database and Excel files







# PT-9500PC Industrial Labeling Solutions

### **Asset Management**

Making "property of" and other asset management tags to protect your valuable assets has never been easier. With easy to use PT-editor software features like:

- 16 built-in industry standard protocols
- Database connect connect P-touch label templates with your databases to create custom labels with YOUR specific company data
- Automatic serialization making tasks like labeling warehouse bins easy

And with our **Tamper Evident Laminated labels**, you can create asset management tags that leave a distinctive pattern when removed. Now your assets and your company can be protected.



Batch 1037 14:24 1/27/03

Property of KM&A Serial # 125037

### **Telecommunications**

Patch panels, faceplates and switches come in varying sizes and layouts. With the PT-9500PC, creating custom templates to create labels for your specific telecommunication equipment is simple. Simply use:

- Built-in sample telecom and datacom templates and input your data and print labels
- Included industry specific symbols to customize the look and feel of your label
- Easy editing features to create custom label templates
- Print options to create labels that contain rotated, vertical and horizontal text

Use in conjunction with our **Extra-Strength Adhesive laminated tapes** that adhere securely to rough, textured and powder-coated surfaces and our **Flexible ID laminated tape** for wrapping and flagging.



TYPE 1 ENCLOSURE SERIES G3
MAINS: 100 Amp. Max. 120/240 VAC 1 Ph. 3W.
CAUTION USE ONLY NO. 2 THROUGH NO. 7 CIRCUIT POSITIONS, DO NOT
REMOVE THISTOUTS NUMBERED 1 OR 8 REMOVE THISTOUTS ONLY
WHEN OPCULTS ARE INSTALLED, CLOSE UNUSED CIRCUIT SHEAKERS
OPENINGS WITH FLUER PLATES.





7W01-F1

# **Manufacturing and General Office**

In any manufacturing location, the ability to print labels that withstand the harshest of environments with a machine that can handle the dirt, grease, grime and common industrial solvents, like acetone, is essential. With the PT-9500PC, the capability to produce labels to handle all of these conditions is covered. Utilizing the PT-9500 capabilities to:

- Print laminated labels from 1/4" to 1 1/2" wide
- Print up to 16 lines on a single label
- Print at fast speeds up to 20 mm/second
- Print strips of easy-peel labels for minimized tape waste and easy tape peeling
- Print multiple labels with the repeat print function

And when used with our **Standard Adhesive laminated tapes** – available in a wide range of colors and styles – that withstand temperatures from -30 to 100 degrees C, these labels are ideal for the harshest of conditions – inside or out.

