intellifAX-4100e

HIGH-SPEED BUSINESS-CLASS LASER FAX



Featuring

- 33.6K bps Super G3 Fax Modem
- 8MB Memory (up to 500 pages1)
- 30-Page Auto Document Feed Capacity
- Front-Loading, 250-Sheet Paper Capacity

At your side.

Of Colonial At your side.

intelliFAX-4100e

HIGH-SPEED BUSINESS-CLASS LASER FAX



Fax

Tele

Technical Specifications

Technical Specifications		
		IntelliFAX-4100e
ĸ	Modem Speed / Best Transmit Speed ¹	33.6K bps / 3 sec.
	Auto Document Feed Capacity	30 pages
	Paper Capacity	250 sheets standard Optional 2nd 250 sheet tray²
	Memory Capacity (max pages ¹)	8 MB (500)
	Broadcasting Locations	Up to 182
	Group Dial / Batch Transmission	Yes (up to 6) / Yes
	Quick Scan¹ (best speed)	Yes (2 sec. per pg.)
	Remote Fax Retrieval	Yes
	Fax Forwarding / Paging	Yes / Yes
	Dual Access	Yes
	Fax Compatibility	Group ITU-T Super G3
	Compression Method	MH / MR / MMR
	Recording Paper Size	8.5" x 11" / 8.5" x 14"
	Grayscale	64 shades
	Delayed Transmission / Polling	Yes / Yes (up to 50 timers)
ephone	Telephone Handset	Yes
	Caller ID / Distinctive Ring Ready ⁶	Yes / Yes
	One Touch / Speed Dial Locations	32 / 100
ру	B&W Copying	Yes
	Copy Speed	Up to 15cpm
	Copy Resolution (max dpi)	Up to 600 dpi class
	Multi-Copying / Sorting	Up to 99 / Yes
	Reduction/Enlargement	50% – 200%
ner	PC Interfaces (standard)	USB ⁴ , Bi-directional Parallel Centronics
	Unit Dimensions (W" x D" x H")	17.4" x 17.1" x 12.7"
	Carton Dimensions (W" x D" x H")	22.0" x 20.3" x 18.1"
	Unit / Carton Weight (lbs.)	23.3 lbs./36.3 lbs.
	UPC Code	0 12502 61639 9

Optional Supplies and Accessories²

TN430: Standard Yield Toner Cartridge (approx. 3,000 pages @ 5%)

TN460: High Yield Toner Cartridge

(approx. 6,000 pages @ 5%)

DR400: Replacement Drum Unit LT400: Second Lower Paper Tray U

Second Lower Paper Tray Unit (additional 250 sheet capacity)



- Based on Brother #1 Chart with MMR coding and standard resolution.
- ² Requires additional purchase.
- $^{\scriptscriptstyle 3}$ Based on 5% page coverage using optional TN460 Toner Cartridge (requires additional purchase).
- ⁴ Built-in USB 1.1, compatible with USB 2.0. Cables not included.
- ⁵ Free printer drivers available for download from Brother Web site.
- ⁶ Contact local phone company for service availability.

© 2006 BROTHER INTERNATIONAL CORPORATION, 100 Somerset Corporate Blvd., Bridgewater, NJ 08807-0911 All trademarks and registered trademarks referenced herein are the property of their respective companies. For more information please visit the Brother Web site at http://www.brother.com. All specifications are subject to change without notice. Printed in USA. CATFX4100E

Key Features at a Glance

- 33.6K bps Super G3 Fax Modem
- 8MB Memory Stores up to 500 Pages¹ for Out-of-Paper Reception and Memory Transmission



- 30-Page Auto Document Feed Capacity
- Front-Loading, 250-Sheet Paper Capacity (adjustable for letter or legal size paper)
- Optional Second 250-Sheet Lower Paper Tray available²
- Dual Access capability lets you scan faxes into memory as fast as 2 seconds/page¹ while the unit is busy sending or receiving
- High-Yield Toner Cartridges deliver lower cost per page³
- 132-Station Auto Dialing (32 One-Touch Keys, plus 100 Speed Dial Locations)
- Fax Broadcasting to up to 182 locations
- Fast and efficient Copying at up to 15cpm with Sorting, Enlargement and Reduction





Other Standard Features

- Built-in Parallel and USB⁴ Interfaces for future printing capability⁵
 - Up to 15ppm print speed
 - Up to 600 x 600 dpi resolution
- Auto Fax/Tel Switching for receiving fax and voice calls on a single phone line
- Fax Forwarding, Paging and Remote Fax Retrieval
- Document Memory Back-up (up to 4 days)
- Caller ID and Distinctive Ring Detection ready⁶

