intelliFAX®-4100 LASER

BUSINESS CLASS FAX, PHONE & COPIER

FEATURING

- **14.4K bps Fax Modem**
- **Up to 15 ppm Laser Engine for printing Faxes and Copies**
- **8MB Memory Stores up to 500 Pages* for Out-of-Paper Reception and Memory Transmission**
- **30-Page Auto Document Feeder**
- **250 Sheet Paper Capacity**

8MB MEMORY with **BROADCASTING**

DUAL ACCESS
Scan a fax into memory while another is being sent or received.

250 SHEET PAPER CAPACITY
Optional 250 Sheet 2nd paper tray available.**

brother

At your side.™

®

intelliFAX-4100

LASER

BUSINESS CLASS FAX, PHONE & COPIER

Featuring...

- 14.4K bps Fax Modem
- Up to 15 ppm Laser Engine for printing Faxes and Copies
- 8MB Memory Stores up to 500 Pages* for Out-of-Paper Reception and Memory Transmission
- 30-Page Auto Document Feeder
- 250 Sheet Paper Capacity (adjustable for letter or legal paper)
- Optional second 250 Sheet Lower Paper Tray Unit** available
- Quickly scan faxes as fast as 2 seconds/page*
- 132 Station Auto Dialing (32 One-Touch Keys, plus 100 Speed Dial Locations)
- High Yield Toner Cartridges deliver low printing costs per page†
- Fax Broadcasting to up to 182 locations
- Multi-Copying up to 99 copies, plus Sorting
- Copy Reduction and Enlargement, 50%-200%

8MB MEMORY with BROADCASTING

250 SHEET PAPER CAPACITY

14.4K bps High Speed Fax Modem

Other Standard Features

DUAL ACCESS — Scan a fax into memory while another is being sent or received.

UP TO 6,000 PAGE† YIELD TONER

- Dual Access capability lets you scan faxes into memory while the unit is busy sending or receiving
- Auto Fax/Tel Switching for receiving fax and voice calls on a single phone line
- Fax Forwarding, Paging and Remote Fax Retrieval
- Caller ID and Distinctive Ring Detection ready††
- Telephone Handset
- Built-in Parallel and USB interfaces for future printing needs▼

PRODUCT SPECIFICATIONS

Approved:	UL and FCC
Unit Dimensions:	17.4″ x 17.1″ x 12.7″
Unit Weight:	23.3 lbs.
Carton Dimensions:	22.0″ x 20.3″ x 18.1″
Carton Weight:	36.3 lbs.
UPC Code:	0 12502 60298 9
Compatibility:	ITU-T Group 3
Coding Method:	MH/MR/MMR
Modulation:	14400/12000/9600/7200/4800/2400 bps
Transmission Time:	As fast as 6 seconds per page*
Printing Method:	Electrophotography
Copy Speed:	Up to 15 copies per minute
Document Input Width:	5.8″ to 8.5″
Recording Paper Size:	8.5″ x 11″ / 8.5″ x 14″
Scanning/Recording Width:	8.2″
Resolution Standard:	203 x 98 lines/inch
Fine Mode:	203 x 196 lines/inch
Superfine:	203 x 392 lines/inch
Display:	LCD, 2 lines by 16 characters
Gray Scale:	64 shades
Interfaces (Standard)	USB and High-Speed, Bi-Directional, Parallel Centronics
Dialing System:	Selectable Pulse/Tone
Speaker Type:	Monitor
Communication Source:	Public Switched Telephone Network
Connection Requirements:	USOC RJ11C Modular Jack (or equivalent)
Power Supply:	120V, 50/60 Hz
Power Consumption:	Sleep Mode: 10W or less Standby: 70W or less Avg. Operating (copying): 350W or less
Noise Level:	53 dBa Printing 30 dBa Standby
Operating Environment::	50° to 90.5° F
Standard Toner Cartridge:	Up to 3,000 pages @ 5% coverage

OPTIONAL ACCESSORIES**

TN430:	Standard Yield Toner Cartridge (Up to 3,000 pages @ 5% coverage)
TN460:	High Yield Toner Cartridge (Up to 6,000 pages @ 5% coverage)
DR400:	Replacement Drum Unit
LT400:	Second Lower Paper Tray Unit (Additional 250 sheets)

* Based on Brother #1 Chart with MMR coding and standard resolution.

** Requires additional purchase.

† Based on 5% page coverage using optional TN460 Toner Cartridge (cartridge requires additional purchase).

†† Contact local phone company for availability of and charges for these serves.

▼ Printer Driver available at www.brother.com

All trademarks and registered trademarks referenced herein are the property of their respective companies.

brother At your side.™

www.brother.com